

Proposed Summit Raceway Rules Changes

By-Laws

Recommend the following changes to the by-laws:

- 1) After becoming a member, there will be a 30 day probation period before the new member is allowed to vote. Exception to this will be if the membership is paid at the time of general membership renewal.
- 2) D.O.C. is to be voted on and approved by the general membership. An alternate will also need to be approved.
D.O.C. nominees will be added to the ballot along with Board of Directors.
- 3) Remove all:
 Protest Procedure (Mechanical)
 Protest Procedure (Procedural)

These are rules governing track running procedure and are covered in the Track General Rules. The By-Laws should cover only Governance Procedure Only!

- 4) Rookie of the year honors will be awarded to the Rookie that finishes highest in the championship points standings (provided they drive the minimum of 50% of the main events).

Track Rules

- ** The track rules as posted on the web site need to be cleaned up and put into proper order to match the rule book.**

Safety

#1 Enforce the “Half White” rule.

#8 Carburetor Throttle Springs:

 GEN-X cars with Fuel Injection or Throttle Body Exempt.

#10 Drive Shaft Hoop:

 GEN-X Exempt due to front wheel drive.

#12 Exhaust System:

 Change to “Exhaust must exit further back than drivers seat in a safe manner. Except IMCA Modifieds, which must conform to IMCA rules.”

#13 Fire Extinguishers:

Fire extinguisher in car is optional. Each cars pit must have a fully charged A.B.C. rated minimum 5lb. fire extinguisher with their cars number clearly marked on it.

#15 Fuel Systems:

G) All cars must have either a safety fire wall between the driver and the fuel cell, or a “Flapper Valve” installed in fuel cell.

#23 Roll Cage:

- A) Minimum 6 point roll cage for Pro-stock and Modified Mini. 4 point roll cage for Pure-stock and GEN-X. IMCA as per IMCA rules.
- D) Pure-Stock: 1 ½” dia. .095” wall Steel Tubing allowed, or 1 ¾” black pipe. No galvanized pipe or pipe fitting will be allowed
- E) Pro Stock: 1 ½” dia. .095 wall Steel Tubing allowed, or 1 ¾” black pipe. No galvanized pipe or pipe fitting will be allowed
- H) Add: Recommend 1/16” plate to be added to drivers side for added driver protection.

#24 Seats:

B) **Replace with:** High Back Racing seat Mandatory. Recommend Aluminum Racing Seat.

#30 Window Nets:

- A) (Need to define “fishnet type”. Maybe add “No string type”

Racing Procedures

#2 Number of laps for races.

Should be determined based on car count.

# of cars		Laps
3-4	=	15
5-8	=	20
9-15	=	25
16 or more	=	30

*May be changed by D.O.C. to improve the show.

#7 Remove this rule from the rule book. (If you need a tow or push, wave a white flag.)

**Need to add to rules:

Predetermined set number of cars to run per heat race.

Track Rules

#6 Protests:

The rule book is inconsistent with the bylaws with fines and timeline. Recommend that rule book be changed to match the By-Laws.

#7 Drivers Responsibilities:

B) Recommend to remove part of the second sentence: “for no money or points”.

C) Add the following:

Points will be awarded to the car provided the registered driver assigned to the number has raced in at least 80% of the main events for the season. If a driver does not participate in the minimum amount of main events, the following penalty, or penalties, will apply: Last place points will be given for each night the car does not meet the minimum amount of main event races. (Note: the driver **will** receive the winnings for the position they placed in for the night.)

D) Recommend to replace the wording to:

All classes except GEN-X must do their share of wheel packing of the track. All cars must complete a minimum of five (5) laps of packing. Failure to do so will result in that car starting in the back of all events. Track officials may waive this only for a good reason. A substitute driver will be allowed, but not a substitute car.

Proposed ECAR Class Rule Changes

GEN-X

#6) Engine:

C) Change rule to allow DOHC

#7) Exhaust:

A) Change web site to match rule book. (Muffler required)

#10) Radiator:

A) Change web site to match rule book. (**add**: “In stock location”)

#12 Seats:

A & C) Change web site to match rule book. (High back racing seat Mandatory.) **Add**: Recommend Aluminum Racing Seat.

Proposed ECAR Class Rule Changes

Pure-Stock

#5 Carburetion:

B) Change wording to: Unmodified Holly 4412 allowed. (Brian Thorp to comment. Wording to be same as other N. NV. Tracks)

#6 Engines:

C) Change to: “No solid or roller cams allowed.”

#8 Frame:

D) Fire extinguisher optional in car.

#11 Roll Cage:

E) Change to same as recommended for general rules changes.

#12 Seats:

B) High back racing seat mandatory. Aluminum seat recommended.

#15 Tires:

C) **Change** to state that tire size allowed is based on tire width that is printed on the sidewall for ease of tech inspection. Maximum P235.

#18 Wheelbase:

A) Change minimum wheelbase to 107.5”.

#19 Wheels:

A) Change wording to include “reinforced center stock **steel** wheels are allowed.”

Proposed ECAR Class Rule Changes

Modified Mini

#8 Frame:

B) Frame connectors allowed. (Needs to be added to the web site. Already in rule book.)

#9 Fuel:

A) Change to: Gasoline only. No Alcohol or Methanol.

D) Add: "Or must have a fire wall between driver and fuel cell.

G) Fire extinguisher in car is optional.

#11 Roll Cage:

K) Change to same as recommended for general rules changes.

#15 Tires:

D) Change web site to match rule book. "No brand name racing tires allowed.

#18 Wheels:

B) Change wording to: Wheel spacers allowed (one per wheel) not to exceed 1".

C) Change to: Bead locks are allowed, right rear wheel only.

Safety rule: Fire retardant neck brace required. (might add to Track Safety Rules for all classes)

Proposed ECAR Class Rule Changes

Pro-Stock

#1 Battery:

C) Add: Battery must be tied down with metal strap or tee bar.

#2 Body:

E) Remove this rule. It would allow for crossovers.

#6 Engines:

F) Change to: Allow roller rockers.

#7 Exhaust:

A) Allow cross over headers (no zoomies or 180 degree headers)

#8 Frame:

** Allow 2 x 3 .095 wall tube chassis from stock front clip back, must be over slung.

#9 Fuel:

A) Gasoline only. No alcohol or methanol.

G) Fire extinguisher in car is optional.

#11 Roll Cage:

B) Change to same as recommended for general rules changes.

#12 Seats:

High back racing seat is mandatory. Aluminum recommended.

#13 Steering:

** Allow heim joint and swedge tube for steering rod assemblies.

#14 Suspension:

** Need to add "N" and "O" to web site. Already in rule book.

** Allow 3 link setup.

** Allow after market upper and lower rear control arms, box tubing only, no swedge tubes or heim joints, non adjustable.

#15 Tires:

C) Change web site to match rule book.

** Allow tire of choice no less than 40 durometer.

#16 Transmission and Drivetrain:

B) Change to: Multi disc clutch or internally clutched transmission allowed.